

**LAMINEX COMPACT LAMINATE (HIGH PRESSURE LAMINATES >= 2MM)**

Chemwatch Independent Material Safety Data Sheet

Issue Date: 17-Jun-2011  
C9317EC

CHEMWATCH 4757-60  
Version No:2.0

**Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME**

LAMINEX COMPACT LAMINATE (HIGH PRESSURE LAMINATES >= 2MM)

**SYNONYMS**

"Laminex Multipurpose Compact Laminate", "Innovations Compact Laminate", "Laboratory Compact Laminate", "XR Grade Compact Laminate", "Alfresco Compact Laminate", Aquapanel

**PRODUCT USE**

■ Used according to manufacturer's directions.

**SUPPLIER**


Company: The Laminex Group  
Address:  
1 O'Rorke Road  
Penrose  
Auckland, 1642  
New Zealand  
Telephone: 0800 303 606  
Fax: 0800 303 707  
Website: [www.thelaminexgroup.co.nz](http://www.thelaminexgroup.co.nz)

**Section 2 - HAZARDS IDENTIFICATION**

**STATEMENT OF HAZARDOUS NATURE**

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.

**CHEMWATCH HAZARD RATINGS**



**RISK**

•None under normal operating conditions.

**SAFETY**

Safety Codes  
S22  
S24

Safety Phrases  
• Do not breathe dust.  
• Avoid contact with skin.

### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
manufactured as a laminate paper as cellulose	9004-34-6	>60
phenol/ formaldehyde resin	9003-35-4	10-<30
following curing of the laminate small amounts of formaldehyde. may be released	50-00-0	NotSpec

### Section 4 - FIRST AID MEASURES

#### SWALLOWED

- - Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

#### EYE

- If this product comes in contact with eyes:
- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
- Generally not applicable.

#### SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

#### INHALED

- - If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

#### NOTES TO PHYSICIAN

- Treat symptomatically.

### Section 5 - FIRE FIGHTING MEASURES

#### EXTINGUISHING MEDIA

- - Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

#### FIRE FIGHTING

- - Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use water delivered as a fine spray to control fire and cool adjacent area.

#### FIRE/EXPLOSION HAZARD

- Combustible. Will burn if ignited.
- Combustion products include: carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>), and minor amounts of, hydrogen cyanide, other pyrolysis products typical of burning organic material.

#### FIRE INCOMPATIBILITY

- - Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

**HAZCHEM**

None

**PERSONAL PROTECTION**

Glasses:

Chemical goggles.

Gloves:

PVC chemical resistant type.

Respirator:

Type BAX- P Filter of sufficient capacity

**Section 6 - ACCIDENTAL RELEASE MEASURES****MINOR SPILLS**

- - Clean up all spills immediately.
- Secure load if safe to do so.
- Bundle/collect recoverable product.
- Collect remaining material in containers with covers for disposal.

**MAJOR SPILLS**

- Minor hazard.
- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment as required.
- Prevent spillage from entering drains or water ways.
- Minor hazard.
- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear physical protective gloves e.g. Leather.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

**Section 7 - HANDLING AND STORAGE****PROCEDURE FOR HANDLING**

- - Avoid generating and breathing dust
- Avoid contact with skin and eyes.
- Wear nominated personal protective equipment when handling.
- Use in a well-ventilated area.

**SUITABLE CONTAINER**

- No restriction on the type of containers. Packing as recommended by manufacturer.

**STORAGE INCOMPATIBILITY**

- - Avoid reaction with oxidising agents.

**STORAGE REQUIREMENTS**

- Store away from incompatible materials.

**Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION****EXPOSURE CONTROLS**

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Notes
Australia Exposure Standards	cellulose (Cellulose (paper fibre) (a))		10			(see Chapter 14)
Australia Exposure Standards	Formaldehyde (Formaldehyde (h))	1	1.2	2	2.5	Sen

The following materials had no OELs on our records

- phenol/ formaldehyde resin

CAS:9003- 35- 4

## PERSONAL PROTECTION

### RESPIRATOR

- type bax-p filter of sufficient capacity.

### EYE

- - Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

### HANDS/FEET

- - Wear chemical protective gloves, eg. PVC.
  - Wear safety footwear or safety gumboots, eg. Rubber.
- NOTE:
- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
  - Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

### OTHER

- - Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.

Avoid breathing dust when sawing or grinding.

Wood dusts produce dermatitis and an increased risk of upper respiratory disease. Epidemiological studies in furniture workers show an increased risk of lung, tongue, pharynx and nasal cancer.

Impairment of nasal mucociliary function may occur below 5 mg/m<sup>3</sup> and may be important in the development of nasal adenocarcinoma amongst furniture workers exposed to hardwoods.

When cutting wear approved dust respirator to avoid inhalation of wood dust created during the cutting process.

### ENGINEERING CONTROLS

- General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

The products are manufactured as high pressure laminates, ranging in thickness up to 2mm. Newly manufactured laminates and freshly cut surfaces may have an odour due to the resin.

### PHYSICAL PROPERTIES

Solid.

Does not mix with water.

Sinks in water.

State	Solid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Immiscible
Flash Point (°C)	Not Available	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Applicable
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	1.1- 1.5

Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Applicable

## Section 10 - STABILITY AND REACTIVITY

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Product is considered stable and hazardous polymerisation will not occur.  
For incompatible materials - refer to Section 7 - Handling and Storage.

## Section 11 - TOXICOLOGICAL INFORMATION

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

- - Generally not applicable.

#### CHRONIC HEALTH EFFECTS

- - Generally not applicable.

### TOXICITY AND IRRITATION

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

#### FORMALDEHYDE:

##### PHENOL/ FORMALDEHYDE RESIN:

- Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type.

##### FORMALDEHYDE.:

##### CELLULOSE:

- Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a nonallergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound.

##### LAMINEX COMPACT LAMINATE (HIGH PRESSURE LAMINATES >= 2MM):

- Not available. Refer to individual constituents.

##### CELLULOSE:

##### TOXICITY

Oral (rat) LD50: >5000 mg/kg

Dermal (rabbit) LD50: >2000 mg/kg

##### IRRITATION

Nil Reported

##### PHENOL/ FORMALDEHYDE RESIN:

##### TOXICITY

Oral (rat) LD50: >2500 mg/kg

Dermal (rabbit) LD50: >5000 mg/kg

##### IRRITATION

Skin (rabbit): 3/8 - Moderate - Draize

Eye(rabbit):40/110 Moderate - Draize

[Manufacturer Mon]

- The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).

This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis.

##### FORMALDEHYDE.:

##### TOXICITY

Oral (woman) LDLo: 108 mg/kg

Oral (man) TDLo: 643 mg/kg

Oral (rat) LD50: 100 mg/kg

Inhalation (man) TCLo: 0.3 mg/m<sup>3</sup>

Inhalation (rat) LC50: 203 mg/m<sup>3</sup>

Dermal (rabbit) LD50: 270 mg/kg

##### IRRITATION

Skin (human): 0.15 mg/3d- I Mild

Skin (rabbit): 2 mg/24H SEVERE

Eye (human): 4 ppm/5m

Eye (rabbit): 0.75 mg/24H SEVERE

■ The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.  
The material may produce severe skin irritation after prolonged or repeated exposure, and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) thickening of the epidermis.</>.

WARNING: This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS. Tenth Annual Report on Carcinogens: Substance anticipated to be Carcinogen [National Toxicology Program: U.S. Dep.

**SENSITISER**

phenol/ formaldehyde resin	Australia Final Report on Hazard Classification of Common Skin Sensitisers	Recommended for Hazard Classification (R43)	No
----------------------------	--	---	----

**Section 12 - ECOLOGICAL INFORMATION**

No data

**Ecotoxicity**

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
Laminex Compact Laminate (high pressure laminates >= 2mm) cellulose	No Data Available LOW	No Data Available No Data Available	LOW	HIGH
phenol/ formaldehyde resin	No Data Available	No Data Available		
formaldehyde	LOW	LOW	LOW	HIGH

**Section 13 - DISPOSAL CONSIDERATIONS**

- - Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

**Section 14 - TRANSPORTATION INFORMATION**

**HAZCHEM:**  
None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: ADG7, UN, IATA, IMDG

**Section 15 - REGULATORY INFORMATION**

POISONS SCHEDULE None

**REGULATIONS**

**Regulations for ingredients**

**cellulose (CAS: 9004-34-6,68442-85-3) is found on the following regulatory lists;**  
"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD Representative List of High Production Volume (HPV) Chemicals"

**phenol/ formaldehyde resin (CAS: 9003-35-4) is found on the following regulatory lists;**  
"Australia Final Report on Hazard Classification of Common Skin Sensitisers", "Australia Inventory of Chemical Substances (AICS)"

**formaldehyde. (CAS: 50-00-0) is found on the following regulatory lists;**

"Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - disinfection by-products)", "Australia - Australian Capital Territory Environment Protection Regulation Pollutants entering waterways - Domestic water quality", "Australia - Queensland Hazardous Materials and Prescribed Quantities for Major Hazard Facilities", "Australia Dangerous Goods Code (ADG Code) - Goods Too Dangerous To Be Transported", "Australia Exposure Standards", "Australia Exposure Standards Currently Under Review", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Illicit Drug Precursors/Reagents - Category II", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Chemical Secretariat (ChemSec) REACH SIN\* List (\*Substitute It Now!) 1.0", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water"

**No data for Laminex Compact Laminate (high pressure laminates >= 2mm) (CW: 4757-60)**

<b>Section 16 - OTHER INFORMATION</b>
---------------------------------------

**INGREDIENTS WITH MULTIPLE CAS NUMBERS**

Ingredient Name	CAS
cellulose	9004- 34- 6, 68442- 85- 3

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references. A list of reference resources used to assist the committee may be found at: [www.chemwatch.net/references](http://www.chemwatch.net/references).

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether

the reported Hazards are Risks in the workplace or other settings.

•The following is a list of Aryl Amines that may be formed by reductive cleavage of cellulose(9004- 34- 6)

AMINE	CAS
-------	-----

•The following is a list of Aryl Amines that may be formed by reductive cleavage of phenol/ formaldehyde resin(9003- 35- 4)

AMINE	CAS
-------	-----

•The following is a list of Aryl Amines that may be formed by reductive cleavage of formaldehyde.(50- 00- 0)

AMINE	CAS
-------	-----

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 17-Jun-2011

Print Date: 17-Jun-2011

*This is the end of the MSDS.*